

Wheel Features

Tread Material:	High Strength PP	Core Material:	High Strength PP
Bearing:	Without Bearing	Tread Hardness:	75D±3
Temperature:	-20°C~50°C	Running Speed:	3.2km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ New polypropylene reinforced modification, economic and durable
- ✔ No deformation, anti-aging, endurable to humid environment
- ✔ The wheel is thick and beautiful in design
- ✔ This product has passed ROHS certification






Rolling resistance	■ ■ ■ ■ ■	Excellent
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ ■ □ □ □	Acceptable
Floor surface preservation	■ ■ □ □ □	Acceptable


Bracket Features

- ✔ The plate is thick and durable
- ✔ Original grease, smooth rotation, low noise
- ✔ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours
- ✔ The riveting structure is optimized and the clearance is stable
- ⚠ Wheel brake only, without direction lock function


Parameter (mm)	Capacity (KG)	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius
1"	10 kg	25	13	35	12	24.5
1.25"	16 kg	32	13	42	14	30
1.5"	20 kg	38	17	50	17	36
2"	30 kg	50	22	65	23	48
2.5"	40 kg	63	27	82	29	60.5
3"	50 kg	75	27	92	29	66.5




Mounting Drawing




1"-3"Plate Swivel/Brake



1"-1.5"Plate Fixed



2"-3"Plate Fixed



Threaded Stem

Wheel Size (inch)	Wheel Dia. (mm)	Plate Size (mm)	Hole Spacing (mm)	Hole Size (mm)	Wheel Size (inch)	Wheel Dia. (mm)	Plate Size (mm)	Hole Spacing (mm)	Hole Size (mm)
1"	25	38×33	30×24	4.2	1"	25	36×20	29×13	4.2
1.25"	32	38×33	30×24	4.2	1.25"	32	36×20	29×13	4.2
1.5"	38	46×39	36×28	5.2	1.5"	38	46×25	36×15	5.2
2"	50	59×47	46×35	6.2	2"	50	58×40	45×25	6.2
2.5"	63	70×58	55×42	8.3	2.5"	63	70×47	55×28	8.3
3"	75	70×58	55×42	8.3	3"	75	70×47	55×28	8.3

Wheel Size (inch)	Wheel Dia. (mm)	Threaded Stem (mm)
1.5"	38	M8×15
2"	50	M10×15
2.5"	63	M12×25
3"	75	M12×25

Product ID

Product Images



Wheel Size

Plate swivel

Plate fixed

Plate swivel brake

Threaded stem

Threaded stem brake

1"

10A01-1001

10A02-1001

-

-

-

1.25"

10A04-1002

10A05-1002

-

-

-

1.5"

10A07-1003

10A09-1003

10A08-1003

10A10-1003

10A11-1003

2"

10A12-1004

10A14-1004

10A13-1004

10A15-1004

10A16-1004

2.5"

10A17-1005

10A19-1005

10A18-1005

10A20-1005

10A21-1005

3"

10A22-1006

10A24-1006

10A23-1006

10A25-1006

10A26-1006

Product Details



High grade modified polypropylene material.

High-purity grease, smooth rotation, can be detected by ROSH.



[English]

