

Wheel Features

Tread Material:	Rubber	Core Material:	Nylon
Bearing:	Single Ball Bearing	Tread Hardness:	75A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ Precision ball bearing, flexible rotation
- ✔ Natural rubber material, injection bonding molding, high rebound
- ✔ Environmental protection, quiet, effectively protect the floor
- ⚠ High temperature and humidity may shortened service life






Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ □	Very good
Operating noise	■ ■ ■ ■ ■	Excellent
Floor surface preservation	■ ■ ■ ■ ■	Excellent

Bracket Features

- ✔ ON/OFF pedals, stable braking effect, easy to operate
- ✔ Bracket made of pressed steel plate, firm and strong
- ✔ Thickened top plate, resistant to compress which is hard to deform
- ✔ Reinforced riveted, close gap, high structural strength
- ✔ Dustproof ring effectively protects grease for long service life
- ✔ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
3"	80 kg	75	32	108	34	71.5	116.5
4"	90 kg	100	32	135	32	82	116
5"	120 kg	125	32	160	32	94.5	121



[English]

Mounting Drawing




Plate Swivel





Plate Fixed



Threaded Stem

Product ID					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
3"	20A01-1538	20AB1-1538	20A3B-1538	20A04-1538	20A7B-1538
4"	20A19-1539	20AB3-1539	20A5B-1539	20A22-1539	20A9B-1539
5"	20A28-1540	20AB4-1540	20A6B-1540	20A31-1540	20A1B-1540

Product Details

ON/OFF brake is easy to operate.



The gap of fancy riveting is close and the structure is stable. Dust ring can effectively dust and protect grease lubrication.



The surface of the bracket is treated with blue and white zinc, which can meet the salt spray test for 72 hours.



Concave and convex three-dimensional design of the cover is beautiful and anti-winding. The soft natural rubber wheel surface has high rebound properties to protect the ground.



[English]

