

Wheel Features

Tread Material:	PU	Core Material:	PP
Bearing:	Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.



- ✔ 2 precision ball bearings,flexible rotation
- ✔ Injection polyurethane,glue-free self lock structureoil resistance,wear resistance
- ✔ Environmental protection,quiet,effectively protect the floor
- ⚠ Not water-proof,humid environment may accelerate aging of the wheel
- ⚠ Biodegradable material,recommended to use within 1 year of production for best performance





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good



Bracket Features

- ✔ Steel plate pressed and fully welded,firm and strong
- ✔ Top plate and ball tracks are quenched to enhance strength and prolong service life
- ✔ Reinforced riveted,close gap,high structural strength
- ✔ Blue galvanized,ROHS/REACH passed,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain

Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	250 kg	100	45	145	34	84	148
5"	300 kg	125	48	165	38	101	151
6"	350 kg	150	50	190	44	119	154
8"	400 kg	200	50	240	54	154	173



Mounting Drawing



Product ID					
Product Images					
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Threaded stem	Threaded stem brake
4"	35A60-1104	35A62-1104	35A61-1104	35A95-1104	35A96-1104
5"	35A63-1105	35A65-1105	35A64-1105	35A97-1105	35A94-1105
6"	35A66-1106	35A68-1106	35A67-1106	35A93-1106	35A98-1106
8"	35A69-1107	35A71-1107	35A70-1107	35A99-1107	35AA1-1107

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.




Grease nipple is convenient for maintenance. Dust ring can protect the grease and dustproof effectively.



Quenched Ball Track has slight abrasion.

Non-quenched Ball Track' s abrasion and gap clearly.



Comparison after 10000times Rotational test.

