

Wheel Features

Tread Material:	Nylon	Core Material:	Cast Iron
Bearing:	Ball Bearing	Tread Hardness:	75D±3
Temperature:	-30°C~90°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.










- ✔ 2 precision ball bearings,flexible rotation
- ✔ Casting nylon material,high load capacity,low starting force
- ✔ No deformation,anti-aging,endurable to humid environment
- ✔ Painted,anti-rust and anti-corrosion
- ⚠ Hard wheel material,it may damage epoxy flooring.Wheel running may cause some noise.






Rolling resistance	■ ■ ■ ■ ■	Excellent
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ □ □ □	Acceptable
Floor surface preservation	■ ■ □ □ □	Acceptable

Bracket Features

- ✔ Single-piece forged base,fully welded,impact resistance and high load capacity
- ✔ Plane bearing,high load capacity,impact resistance and flexible steering
- ✔ Radial conical bearing,high load capacity and impact resistance
- ✔ Powder spray treatment,superior anti-rust and anti-corrosion performance,salt spray test over 72 hours
- ✔ ON/OFF pedals,stable braking effect,easy to operate
- ✔ Brake part is replaceable,convenient to maintain


Parameter (mm)							
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
5"	700 kg	125	48	175	34	97	151
6"	900 kg	150	50	200	38	113	151
8"	1100 kg	200	50	248	47	147	175
10"	1200 kg	250	62	305	60	185	185
12"	1400 kg	300	62	355	60	210	210




[English]

Mounting Drawing

4"-8"



10"-12"




Product ID						
Product Images						
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Plate swivel	Plate fixed	Plate swivel brake
5"	35B01-1149	35B03-1149	35B02-1149			
6"	35B04-1150	35B06-1150	35B05-1150			
8"	35B07-1151	35B09-1151	35B08-1151			
10"				35B10-1209	35B12-1209	35B11-1209
12"				35B13-1210	35B15-1210	35B14-1210

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Planar bearings and radial conical bearings, with high loading, impact resistance, flexible in rotation.



Double-sided welding, with 10mm thickened plate and 8mm thickened bracket.



Arc wheel is easily move. Iron cover looks nice and anti-winding.



[English]

