## 35B 系列 Supper Nylon (White)




## Wheel Features

Tread Material:	Nylon	Core Material:	Nylon
Bearing:	Ball Bearing	Tread Hardness:	75D±3
Temperature:	-30°C~90°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.

- 2 precision ball bearings,flexible rotation
- 🤣 Injection nylon,high load capacity,high wear resistance
- 💎 No deformation,anti-aging,endurable to humid environment
- 🤣 With metal covers,thread-proof design
- Hard wheel material, it may damage epoxy flooring. Wheel running may cause some noise.








## Bracket Features

- 🐼 Single-piece forged base,fully welded,impact resistance and high load capacity
- 💎 Plane bearing,high load capacity,impact resistance and flexible steering
- 🤣 Radial conical bearing,high load capacity and impact resistance
- 🤣 Powder spray treatment, superior anti-rust and anti-corrosion performance, salt spray test over 72 hours
- ON/OFF pedals, stable braking effect, easy to operate
- 🤣 Brake part is replaceable,convenient to maintain

Parameter	52	$\frown$	П			r	R
(mm)	KG		[]		()	Ŧ	E.
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	450 kg	100	46	150	34	84	151
5"	650 kg	125	46	175	34	97	151
6"	850 kg	150	48	200	38	113	151
8"	1050 kg	200	48	248	47	147	175







[English]

```
1/2
```




## **Supper Nylon (White)**



Mounting Drawing

系列 SERIES



Product ID	and the second		T	
Product Images	Č.	Ċ		
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	
4"	35B26-1645	35B27-1645	35B28-1645	
5"	35B01-1646	35B03-1646	35B02-1646	
6"	35B04-1647	35B06-1647	35B05-1647	
8"	35B07-1648	35B09-1648	35B08-1648	

Product Details

ON/OFF brake is easy to operate. Brake components can be replaced with screw connecting.



Planar bearings and radial conical bearings, with high loading, impact resistance, flexible in rotation.

Double-sided welding, with 10mm thickened plate and 8mm thickened bracket.



Imported POK nylon material, high wear resistance, anti-aging, iron cover, nice appearance and anti-winding.







35B NLXB EN