

Wheel Features

Tread Material:	High Strength PP	Core Material:	High Strength PP
Bearing:	Ball Bearing	Tread Hardness:	75D±3
Temperature:	-25°C~80°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.










- ✔ 2 precision ball bearings, flexible rotation
- ✔ Injection polypropylene, integral injection, low starting force, economical choice
- ✔ No deformation, anti-aging, durable to humid environment
- ⚠ Not wear-resistant material and wheel running may cause some noise.
- ⚠ Hard wheel material, it may damage epoxy flooring





Rolling resistance	■ ■ ■ ■ ■	Excellent
Wear resistance	■ ■ ■ □ □	Good
Operating noise	■ □ □ □ □	Acceptable
Floor surface preservation	■ □ □ □ □	Acceptable


Bracket Features







- ✔ Steel plate pressed and welded, firm and strong
- ✔ Reinforced riveted, close gap, high structural strength
- ✔ Blue galvanized, ROHS/REACH passed, salt spray test over 72 hours
- ✔ Easy to operate, convenient to release the brake
- ✔ Dustproof ring effectively protects grease for long service life

Parameter (mm)	 Capacity	 Wheel Dia.	 Wheel Width	 Total Height	 Offset	 Swivel Radius	 Swivel Radius
Wheel Size	Capacity	Wheel Dia.	Wheel Width	Total Height	Offset	Swivel Radius	Swivel Radius
4"	240 kg	100	42	145	34	84	148
5"	290 kg	125	45	165	38	101	149
6"	340 kg	150	45	190	44	119	150
8"	390 kg	200	45	240	54	154	163



Mounting Drawing



Product ID						
Product Images						
Wheel Size	Plate swivel	Plate fixed	Plate swivel brake	Plate swivel brake	Plate swivel brake	Plate swivel brake
4"	35C01-1152	35C04-1152	35C20-1152	35C65-1152	35C03-1152	35C56-1152
5"	35C05-1153	35C08-1153	35C21-1153	35C66-1153	35C07-1153	35C57-1153
6"	35C09-1154	35C12-1154	35C22-1154	35C67-1154	35C11-1154	35C58-1154
8"	35C13-1155	35C16-1155	35C23-1155	35C68-1155	35C15-1155	35C59-1155

Product Details



Fancy riveting has tight clearance, the structure is stable and high strength.



Dust ring can effectively protect dust and grease lubrication.

The surface treatment of bracket is Zinc plated, blue, which can meet the salt spray test for 72 hours. The bracket is curved shape, nice appearance and high strength.



Reinforced wheel ribs with high strength. Bearing cover is tight clearance.

[English]

