

Wheel Features

Tread Material:	PU	Core Material:	High Strength PP
Bearing:	Single Ball Bearing	Tread Hardness:	95A±3
Temperature:	-20°C~50°C	Running Speed:	4km/h

Note: Use beyond temperature range or beyond the recommended speed may shorten product life or even damage the product.










- ✔ Precision ball bearing, flexible rotation
- ✔ Injection polyurethane, glue-free self lock structure, oil resistance, wear resistance
- ✔ Environmental protection, quiet, effectively protect the floor
- ⚠ High temperature and humidity may shorten service life





Rolling resistance	■ ■ ■ ■ □	Very good
Wear resistance	■ ■ ■ ■ ■	Excellent
Operating noise	■ ■ ■ ■ □	Very good
Floor surface preservation	■ ■ ■ ■ □	Very good

Bracket Features



- ✔ Easy to operate, convenient to release the brake
- ✔ Spindle equipped with precision bearing, quiet and flexible
- ✔ Nylon-injection core, lightweight and tough
- ✔ Galvanized, salt spray test over 48 hours
- ✔ This product has passed TUV certification. Utility model patent owned, protected by intellectual property law.

Parameter (mm)	 Capacity	 Wheel Dia.	 Wheel Width	 Total Height	 Offset	 Swivel Radius	 Swivel Radius
3"	30 kg	75	25	114	24	61.5	84
4"	80 kg	100	32	152	32	82	112



[English]

Mounting Drawing



Product ID				
Wheel Size	Plate swivel	Plate fixed	Threaded stem	Threaded stem brake
4"	80N01-1703	80N02-1703	80N10-1703	80N11-1703
5"	80N04-1704	80N05-1704	80N13-1704	80N14-1704

Product Details



Built-in cover can prevent winding and protect bearings effectively.

Nylon bracket is one - piece injection molding and high strength.



The ergonomic pedal design is optimized to improve the single-pedal brake experience.

